



Premium Low SAPS Engine Oil UNEX TRUCK LX SAE 5W30

PROPERTIES

UNEX TRUCK LX SAE 5W30 is a premium Low SAPS fuel-efficient engine oil for commercial vehicles with and without diesel particulate filter (DPF), EGR and SCR catalysts for NOx reduction. **UNEX TRUCK LX SAE 5W30** features low ash additive technology (Low SAPS = reduced sulfated ash, low phosphorus and sulfur content). By using selected base oils of the latest synthesis technology, the all-season viscosity range SAE 5W-30 preferred by many engine manufacturers is realized. **UNEX TRUCK LX SAE 5W30** allows significantly extended oil change intervals with improved engine protection. The modern "Low SAPS" additivation reduces internal friction in the engine, resulting in lower fuel consumption (fuel economy) with optimized wear protection. The economy is characterized by reduced oil consumption, reduced pollutant emissions, as well as more favorable operating costs. The improved soot carrying capacity contributes significantly to the prevention of abrasive wear in the engine and best engine cleanliness.

APPLICATION INFORMATION

UNEX TRUCK LX SAE 5W30 has been specially developed for the economical supply of exhaust-optimized engines, even under extreme loads. **UNEX TRUCK LX SAE 5W30** is a year-round high-performance commercial vehicle engine oil, for Euro IV, V and VI engines and enables maximum oil change intervals. The engine oil maintains the effectiveness of the exhaust gas purification systems over very long running times. Performance losses due to clogged diesel particulate filters are prevented by lowered particulate emissions and higher efficiency is achieved.

CERTIFICATES AND STANDARDS

- SAE 5W-30 • ACEA E9 / E7 / E6 • API CK-4 / SN • JASO DH-2
- MB 228.51 • Renault VI RLD-3 • MAN M 3477 • Detroit Diesel DDC 93K222 • MB 228.52 • Mack EOS-4.5 • Deutz TTCD • Deutz DQC IV-18 LA • MAN M 3677 • MTU MTL 5044 Typ 3.1 • Caterpillar ECF-3 • Scania Low Ash • Volvo VDS-4.5 (STD 417-0003) • Renault Rn700 • Cummins CES 20086 • Ford WSS-MSC913-C

UNEX TRUCK LX SAE 5W30 is a product of UNEX GmbH. - **MADE IN AUSTRIA**

| Typical Properties | Unit | Test Method | UNEX TRUCK LX SAE 5W30 |
|------------------------|--------------------|-----------------|------------------------|
| SAE Class | | SAE J 306 | 5W-30 |
| Density @ 15°C | g/cm ² | DIN 51 757 | 0,855 |
| Kin. Viscosity @ 40°C | mm ² /s | DIN EN ISO 3104 | 71-72,5 |
| Kin. Viscosity @ 100°C | mm ² /s | DIN EN ISO 3104 | 11,8-12,1 |
| Viscosity Index (VI) | | DIN ISO 2909 | 160-165 |
| Flash Point COC | °C | DIN ISO 2592 | 233 |
| Pour Point | °C | DIN ISO 3016 | -43 |

The figures given may vary within the usual commercial range.

PACKAGING

